

WristOx₂[®] Model 3150

Wrist-worn Pulse Oximeter



The WristOx₂ Model 3150 Pulse Oximeter is Unmatched for Performance and Value!

Engineered with Nonin Medical's proven PureSAT[®] SpO₂ technology, the WristOx₂ Model 3150 delivers highly accurate readings in the widest range of patient populations and settings. The WristOx₂ Model 3150 is ideal for applications including ambulatory monitoring, remote wireless monitoring and overnight studies—providing the versatility and reliability that clinicians expect from Nonin. The most advanced wrist-worn pulse oximeter available, the WristOx₂ Model 3150 features improved performance and reporting capabilities, including enhanced connectivity and increased memory storage. A new ergonomic design and Bluetooth[®] wireless technology eliminate the inconvenience of bulky cables and provide patients with increased comfort and independence—making this pulse oximeter ideal for ambulatory monitoring.

WristOx₂ Model 3150

Product Highlights

- **Easy to Use** – Simply put your finger in the sensor
- **Design Updates** – Small size wears like a watch with large display screen and enhanced sensor connector design
- **Software Support** – Advanced features such as 6 Minute Walk Test (6MWT) or overnight oximetry reporting available when used with nVISION® data management software
- **Convenient Data Transfer** – Transfer data securely to nVISION® via Bluetooth wireless or USB connection
- **WristOx Sensor Line** – The WristOx₂ sensors are exclusively designed for use with the WristOx₂ Model 3150



Added Benefits

Versatility – The WristOx₂ Model 3150 is an ideal choice for multiple applications where small, portable oximetry is needed

Powerful Battery – 48 hours of battery life (non-Bluetooth), 24 hours with continuous Bluetooth using two AAA alkaline batteries

Simple Data Verification – The new Memory Volume Indicator Mode provides verification of recorded data during oxygen qualification studies

Enhanced Memory – 1,080 hours of non-volatile memory at a four-second sampling rate with additional high resolution variable sampling options of one or two seconds

Nonin Quality and Support – Rugged durability and industry-leading 3-year warranty

Proven PureSAT® Pulse Oximetry Technology – Fast and accurate response for capturing events in challenging conditions such as motion and low perfusion

Select Your Options

- 8000J-WO2 Adult Flex Sensor, 8000AA-WO2 Clip Sensor, 8000SS-WO2, 8000SM-WO2 and 8000SL-WO2 (small, medium, large) Soft Sensors
- 3150WB – Wristband
- 3150I – Adapter cable (for compatibility with all Nonin PureLight® sensors)
- nVISION data management software
- 3150SC – PC USB interface cable
- WristOxCC – WristOx₂ carrying case



Available in Two Configurations

WristOx₂ (3150) Single unit or Starter Kit (3150SK) with nVISION software, PC USB interface cable and extra wrist straps. System comes with a 8000SM-WO2 Sensor.

Specifications

Dimensions (without sensor or strap)	56 mm (2.2") wide x 74 mm (2.91") high x 20 mm (.79") thick
Weight (with batteries and wrist strap)	.71 grams (2.5 oz)
Warranty	3 years
Oxygen Saturation Range (%SpO ₂)	0% to 100%
Pulse Rate Range	18 to 321 pulses per minute
Displays	
Numeric Displays	3-digit Indicators
Pulse Indicator	Pulse Strength Bar graph
Accuracy	
Blood Oxygen Saturation (%SpO ₂ ±1 A _{mb})*	70 - 100%
Non-motion	± 2 digits**
Low perfusion	± 2 digits**
Motion	± 3 digits***
Pulse Rate (in all 3 listed above)	± 3 digits**
Temperature	
Operating	+23° to +104°F (-5° to +40°C)
Storage/Transportation	-40° to +158°F (-40° to +70°C)
Humidity	
Operating	10% to 95% noncondensing
Storage/Transportation	10% to 95% noncondensing
Altitude	
Operating Altitude	Up to 13,123 feet (4,000 meters)
Hyperbaric Pressure	Up to 4 atmospheres
Power Requirements	Two 1.5V alkaline AAA batteries
Battery Life	
Operating without Bluetooth®	53 Hours Minimum
Operating with Bluetooth®	21 Hours Minimum
Storage	9 months
Memory	
Type	Nonvolatile
Capacity	Up to 1,080 hours @ 4 sec. data storage rate Up to 540 hours @ 2 sec. data storage rate Up to 270 hours @ 1 sec. data storage rate


Classifications per IEC 60601-1/UL60601-1

Type of Protection	Internally powered (on battery power)
Degree of Protection	Type BF-Applied Part
Mode of Operation	Continuous

* ± A_{mb} encompasses approximately 68% of the population.
** Refer to the operator's manual for additional accuracy specifications.
*** As tested with Soft Sensor Series.
Quality systems registered to ISO 13485

Specifications are subject to change without notice.

Authorized Distributor:



©2016 Nonin Medical, Inc. All trademarks are the property of Nonin Medical, Inc. unless otherwise noted. Bluetooth is a registered trademark of Bluetooth SIG, Inc. 7883-001-05

Nonin Medical, Inc.
13700 1st Avenue North
Plymouth, MN • 55441-5443 • U.S.A.
Tel: +1.763.553.9968 1.800.356.8874
Fax: +1.763.577.5521
E-mail: info@nonin.com

Nonin Medical B.V.
Prins Hendriklaan 26
1075 BD Amsterdam • Netherlands
Tel: +31 (0)13-79 99 040
Fax: +31 (0)13-79 99 042
E-mail: infointl@nonin.com

nonin.com

